



ALIEN™

www.alienasia.com



AT870

Warehouse, Pharmaceutical, Parcel Service and etc.

Series Highlights:

- 3.5" Touch LCD
- Windows CE5.0
- Marvell™ PXA 270 520Mhz
- Memory 128MB RAM / 256MB ROM
- 1D or 2D Barcode Reader
- RFID UHF 900MHz GEN2, ISO/IEC 18000-6C / 18000-6B (Option)
- HF 13.56MHz ISO15693, MIFARE, ISO14443 A/B (Option)
- Wireless LAN 802.11 b/g | Modem 2G(GSM/GPRS/CDMA)
- Bluetooth | Camera with Flash | GPS | Cradle | Gun Handle Grip

(주)에일리엔테크놀로지아시아

본 사 : 서울특별시 금천구 디지털로9길 99, 909(가산동, 스타밸리)

전 화 : 707-7012-1317 | 팩스 : 02-868-1710 | MAIL : support@alienasia.com

AT870

Warehouse, Pharmaceutical, Parcel Service and etc.



FRONT



BACK



HF BARCODE READER



UHF GUN READER

ACCESSORIES



Adaptor
AC Cable

Protection
Film

Handstrap

Cradle

GUN Handle

USB Cable

SPECIFICATION

Performance Characteristics

Processor	Marvell™ PXA270 520Mhz
Operating System	3.5" QVGA with Backlight
Memory	TFT LCD, 240x320Pixel, 262,144 Color
Display	95% non-condensing Windows CE 5.0
Weight	RAM 128MB / ROM 256MB
Operating Tem p.	250g (PDA only, without battery)
Storage Temp.	-20°C ~ 60°C
Humidity	-30°C ~ 70°C
Drop Spec.	1.5M Drop to concrete
Dust & Water Proof	IP65

Physical Characteristics

Audio	Mono Speaker, Ear Jack, Microphone
Satandard I/O Port	USB 1.1 Client / USB Host & Serial (RS-232) via gender cable or Cradle
Expansion Slot	1Micro SD Slot (SDHC), 1SIM Slot
Notification	Vibrator and LED, Speaker
Dimensions(L x W x H)	148 x 76 x 25.2 (30.5)mm

Battery Supply

Main Battery	Lithium-Ion Polymer 3.7V 2,960mAh (Rechargeable) Up to 4,400mAh*
Backup Battery	Lithium-Ion Polymer 3.7V 80mAh (Rechargeable)
Power Adapter	Input AC110V ~ 240V / Output DC 5V 3A

Network Characteristics

WLAN	IEEE 802.11 b/g Compliant (Cisco Compatible Extensions Wi-Fi Alliance)
Bluetooth	Class II 2.0, SPP Only
Radio	GSM/GPRS, CDMA*
GPS	Internal Antenna

Data Capture & Data Processing Device

Barcode Engine	1D Laser or 2D Imager Scanner
Camera	1.3 Mega Pixel Fixed Focus with Flash

UHF 900Mhz RFID Reader/Writer

Frequency	860Mhz ~ 960Mhz
Reading range	0M ~ 7M (According to Tag & Environment)
Writing range	0M ~ 3M (According to Tag & Environment)
RF output	1W EIRP
Protocol	EPC Gen2, ISO / IEC 18000-6C, 18000-6B*
Special function	Anti-Collision

HF 13.56Mhz RFID Reader/Writer

Applied RFID Ta g	ISO 15693 Standard , Mifare, ISO 14443 Type A/B
Reading range	Based On Tag : 0 ~ 10Cm

Cradle

Stardard Interface	USB 1.1 Host / USB Client / DC Power Jack / Extra Battery Charger / Serial(RS232) via gender cable
Ethernet Interface	RJ-45 Ethernet Interface*

Accessories*

Gun Handle Grip (Pisto Grip)	Body, UHF / HF Availiable Lithium-Ion 3.7V 4,400mAh(Rechargeable)*
Gun Handle Battery	

Common Accessories and Optinal Accessories

Standard Accessories : Stylus Pen, LCD Protec Flim, Hand Strap
Optional Accessories: Veichle Cradle, Leather Case, Cigar Charger



* Some Funtion and parts will be options / ✕ All Features and specifications described are subject to change without notice.